



NorTorque® Series Adjustable 16mm Spigot Overview

The NorTorque utilises Norbar's proven mechanism and internal components and built them into a purposeful and attractive torque wrench. Accurate to $\pm 3\%$ of reading which meets and exceeds ISO6789.

- Each tool is supplied with a free NATA calibration certificate
- Accurate to $\pm 3\%$ of reading which meets and exceeds ISO6789:2003
- Convenient hanger feature for tool storage also aids wrench unlocking and adjustment
- Push/pull lock is fast and intuitive to use and prevents accidental adjustment of the set torque
- Light and fast adjustment saves operator time and effort
- Micrometer scale applying to the primary torque units (N·m on a dual scale wrench) for simple and error free setting
- Just eight turns to cover the entire scale
- Push through ratchets with a narrow engagement angle of 5° for working in tight spaces

16mm Spigot Adjustable - Dual Scale

SKU	Model	Torque Range	Drive	Length	Weight
130141	60TH	10 - 45lbf ft 12 - 60Nm	16mm Spigot	323mm	0.60kg
130142	100TH	15 - 75lbf ft 20 - 100Nm	16mm Spigot	357mm	0.66kg
130143	200TH	30 - 150lbf ft 40 - 200Nm	16mm Spigot	440mm	0.78kg
130144	300TH	45 - 220lbf ft 60 - 300Nm	16mm Spigot	566mm	1.13kg

16mm Spigot Adjustable - Nm Only

SKU	Model	Torque Range	Drive	Length	Weight
130161	60TH	12 - 60Nm	16mm Spigot	323mm	0.60kg
130162	100TH	20 - 100Nm	16mm Spigot	357mm	0.66kg
130163	200TH	40 - 200Nm	16mm Spigot	440mm	0.78kg
130164	300TH	60 - 300Nm	16mm Spigot	566mm	1.13kg